

BDCOM WBR55G-BS90

Overview

BDCOM WBR55G-BS90 is a high-performance outdoor Wireless Base Station designed for P2MP connectivity. It complies with IEEE 802.11 Wi-Fi standards and equipped with an external dual-polarized high-gain antenna, it delivers reliable wireless bridging over ultra-long distances.

WBR55G-BS90 features a watchdog mechanism for automatic recovery during network disruptions, along with remote management capabilities. Administrators can monitor real-time status, perform firmware upgrades, and initiate reboots from anywhere.

Ideal for long-range wireless backhaul and point-to-multipoint deployments, WBR55G-BS90 combines high throughput, carrier-grade reliability with efficient maintenance for harsh outdoor environments.



Key Features

- Support WiFi5 standard
- Support 5GHz band
- Up to 867Mbps speed
- 2 Gigabit Ethernet ports
- Cover more than 3~5KM radius area

H/W Specification

Model	BDCOM WBR55G-BS90
Chipset	QCA9563+QCA9882+QCA8334
Flash	SPI NOR 16MB
DDR	DDR2 128MB
WiFi Frequency	5.150~5.850GHz
WiFi Protocol	802.11 a/n/ac/wave2
Max rate	867Mbps
Antenna	External Directional antenna

TX Power	802.11a	54M	21±2dBm	6M	25±2dBm
	802.11n HT20	MCS7	21±2dBm	MCS0	25±2dBm
	802.11n HT40	MCS7	21±2dBm	MCS0	25±2dBm
	802.11ac VHT20	MCS9	20±2dBm	MCS0	25±2dBm
	802.11ac VHT40	MCS9	19±2dBm	MCS0	25±2dBm
	802.11ac VHT80	MCS9	19±2dBm	MCS0	25±2dBm
Recv Sensitivity	802.11a	54M	-73dBm	6M	-90dBm
	802.11n HT20	MCS7	-71dBm	MCS0	-89dBm
	802.11n HT40	MCS7	-68dBm	MCS0	-86dBm
	802.11ac VHT20	MCS9	-64dBm	MCS0	-87dBm
	802.11ac VHT40	MCS9	-59dBm	MCS0	-84dBm
	802.11ac VHT80	MCS9	-56dBm	MCS0	-81dBm
EVM	802.11a 54M: ≤ -25 dB 802.11n MCS7: ≤ -28 dB 802.11ac MCS9: ≤ -32 dB				
PPM	±20ppm				
WAN	1*10/100/1000M WAN				
LAN	1*10/100/1000M LAN				
Power	PoE 12V or DC 12V Max≤12W				
Reset	Press 10 seconds for Factory resetting				
button	Set Master / Slave mode				
Indicators	SYS, WAN, LAN, WIFI, Signal*5				
Dimension	186×86×40mm (Antenna: 400×140×28mm)				
Weight	400g (Antenna: 0.5Kg)				
Temperature	Working: -30~55°C Storage: -40~70°C				
Humidity	5~95% (Non-Condensing)				
Protection	IP65				
ESD	Air: ±8KV Touch: ±6KV				
Electrical Surge	Common Mode: 2KV Differential Mode: 1KV				

S/W Specification

Operating mode	<ul style="list-style-type: none">· AP mode· Relay mode
Wireless	<ul style="list-style-type: none">· Multi SSID (Max: 4) and Hidden SSID· Transmit Power Setting· Scheduled WiFi On/Off
Wireless Safety	<ul style="list-style-type: none">· WPA/WPA-PSK· WPA2/WPA2-PSK· MAC ACL with Whitelist· Max client limit (Max: 64)· User isolation
IP Networks	<ul style="list-style-type: none">· Static IP, DHCP client· 802.1Q VLAN· IPv4 & IPv6· DHCPd, SNMP, NTP client
Management	<ul style="list-style-type: none">· SSH, Telnet· Http/Https· SNMP read· Route tracking· Ping watchdog

Antenna Specification

Working Frequency	5180~5850 MHz
Gain	18dBi
Polarization mode	Vertical/horizontal dual polarization
VSWR	<1.8
Beam angle	Horizon: 90° / Vertical: 15°