

DP-22CS54D7T-PH 1080p WDR Covert Camera



Key Features

- 2.0 megapixel progressive scan CMOS
- HD analog output, up to 1080p resolution
- OSD menu, DNR, AGC
- 120 dB true WDR
- Applicable for ATM machine

Specifications

| Camera | |
|------------------------|---|
| Image Sensor | 2.0 megapixel progressive scan CMOS |
| Min. illumination | 0.01 Lux@(F1.2, AGC ON) |
| Signal System | PAL/NTSC |
| Shutter Time | PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s |
| Effective Resolution | 1920 (H) × 1080 (V) |
| Lens | 3.7 mm @ F2.5 (2.8 mm Optional) |
| Field of View | 69.5° (3.7 mm), 78.4° (2.8 mm) |
| Lens Mount | M12 |
| Day & Night | Electronic |
| Frame Rate | 1080p@25fps, 1080p@30 fps |
| Synchronization | Internal Synchronization |
| WDR | > 120 dB |
| Video Output | 1 HD analog output |
| Menu | |
| AGC | High/Middle/Low/ Off |
| Day/Night Mode | AUTO/COLOR/WB (White and Black) |
| White Balance | ATW/MWB |
| Backlight Compensation | Support |
| WDR | Support |
| Function | Contrast, Sharpness, Color gain, Mirror, Digital noise reduction |
| General | |
| Operating Conditions | -40° C to 60° C (-40° F to 140° F) Humidity: 90% or less (no condensation) |
| Power Supply | 12 V DC ± 10% |
| Power Consumption | Max. 1.5 W |
| Dimensions | 32.4 mm × 32.4 mm × 22.0 mm (1.28" × 1.28" × 0.87") |
| Weight | Approx. 200 g (0.44 lb.) |