

## SC-L602M 2MP H.265 Motorized Bullet Camera



### Key Features

- 1/2.8" SONY Starvis Bac- Illuminated CMOS Sensor
- 1945(H)\* 1097(V)
- 2.7-13.5mm
- H.264/ H.264+/ H.265/H.265+/JPEG/AVI/MJEG
- IP66

## Specifications

Camera	
Image Sensor	1/2.8" SONY Starvis Back- Illuminated CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1945(H)*1097(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI/MJEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Lens	
Focus Length	2.7-13.5mm
Focus Control	Auto
Lens Type	Motorized
Pixel	3MP
Night Vision	
Infrared LED	42*x 4PCS
Infrared Distance	60M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45(10/100Base-T)
ONVIF	Support ONVIF 2.4
Protocol	TCP/ IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS DDNS, RTP, RTSP, RTCP, NTP, SMTP
P2P	YES, Support QR Code
POE	Optional, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	1920*1080@30fps
Main Stream 2	/
Main Stream 3	/
Sub Stream 1	720*480@30fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	Iphone, Ipad, Android, Android Pad

<b>Camera Features</b>	
Day/Night	Color / B&W (IR-CUT)
Starling	/
Corridor Pattern	/
Image Config	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control)
Defog Mode	Support
ROI	/
BLC	Support
HDR	/
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR / NAS / CMS / Web
Language	Chinese,Simplified,Chinese Traditional,English,Bulgarian,Polish,Farsi,German,Russian French,Korean Portuguese,Japanese,Turkish,Spanish, Hebrew,Italian, Nederlands
<b>Interface</b>	
Audio	Optional
Alarm	/
SD Card Slot	/
RS485	/
<b>General</b>	
Housing	Plastic, IP66
Anti-cut Bracket	Optional
IR Cut Filter	YES
Operation Temperature	-20°C ~+60°C RH95% Max
Storage Temperature	-20°C ~+60°C RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	162(W) x 88 (H) x 86 (D)mm
Weight	600g