

**SC-L604F**  
**4MP H.265 Bullet Camera**



### Key Features

- 1/3" OV High resolution CMOS Sensor
- 2688(H)\* 1520(V)
- 3.6mm (2.8mm/6mm/8mm Optional)
- H.264/ H.265/ JPEG/ AVI/ MJPEG
- IP66

## Specifications

Camera	
Image Sensor	1/3" OV High-resolution CMOS Sensor
Resolution	4MP
Effective Pixels	2688(H)*1520(V)
Compression	H.264/H.265/JPEG/AVI/MJEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Lens	
Focus Length	3.6mm (2.8mm/6mm/8mm Optional)
Focus Control	Fixed
Lens Type	Fixed
Pixel	4MP
Night Vision	
Infrared LED	42 $\mu$ x 4PCS
Infrared Distance	60M
IR Status	Under 10 Lux By CDS
IR Power On	CDS Auto Control
Network	
Ethernet	RJ-45(10/100Base-T)
ONVIF	Support ONVIF 2.4
Protocol	TCP/ IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS DDNS, RTP, RTCP, NTP, SMTP
P2P	YES, Support QR Code
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2560*1440@20fps
Main Stream 2	2304*1296@30fps
Main Stream 3	1920*1080@30fps
Sub Stream 1	720*480@20fps / 720*480@20fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	352*288@20fps / 352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
Smart Phone	Iphone, Ipad, Android, Android Pad

### Camera Features

Day/Night	Color / B&W (IR-CUT)
Starling	/
Corridor Pattern	Support
Image Config	Saturation/Brightness/Contrast/Sharpness, Mirror, 3D NR, White Balance, FLK (Flicker Control)
Defog Mode	Support
ROI	/
BLC	Support
HDR	/
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR / NAS / CMS / Web
Language	Chinese,Simplified,Chinese Traditional,English,Bulgarian,Polish,Farsi,German,Russian French,Korean Portuguese,Japanese,Turkish,Spanish, Hebrew,Italian, Nederlands

### Interface

Audio	Optional
Alarm	/
SD Card Slot	Yes, Support Max 64GB
RS485	/

### General

Housing	IP66
Anti-cut Bracket	Optional
IR Cut Filter	YES
Operation Temperature	-20°C ~+60°C RH95% Max
Storage Temperature	-20°C ~+60°C RH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	162(W) x 88 (H) x 86 (D)mm
Weight	600g